



US005760485A

United States Patent

Shiga et al.

[11] Patent Number: 5,760,485

[45] Date of Patent: Jun. 2, 1998

[54] STARTER

[75] Inventors: Tsutomu Shiga, Nukata-gun; Nobuyuki Hayashi, Nagoya; Masanori Ohmi, Anjo; Sadayoshi Kajino, Nagoya, all of Japan

[73] Assignee: Nippondenso Co., Ltd., Kariya, Japan

[21] Appl. No.: 600,991

[22] PCT Filed: Dec. 19, 1994

[86] PCT No.: PCT/JP94/02166

§ 371 Date: Mar. 1, 1996

§ 102(e) Date: Mar. 1, 1996

[87] PCT Pub. No.: WO96/19662

PCT Pub. Date: Jun. 27, 1996

[51] Int. Cl.⁶ F02N 11/00; H02P 9/04

[52] U.S. Cl. 290/38 R; 290/48

[58] Field of Search 290/38 R, 38 A, 290/38 C, 38 B, 48; 74/6, 7 A, 7 R, 7 E

[56] References Cited

U.S. PATENT DOCUMENTS

4,268,772 5/1981 Workman 310/197
4,481,424 11/1984 Hattori et al. 290/40
4,674,344 6/1987 Kazino et al. 74/7 A

4,819,975 4/1989 Motishita et al. 290/48
4,970,908 11/1990 Isozumi et al. 74/7 E
5,130,596 7/1992 Umeki 310/234
5,508,566 4/1996 Nagao et al. 290/38 R

FOREIGN PATENT DOCUMENTS


387 073 9/1990 European Pat. Off. .
387 666 9/1990 European Pat. Off. .
0 582 429 2/1994 European Pat. Off. .
582 429 2/1994 European Pat. Off. .
2 614 363 10/1988 France .
3-115776 5/1991 Japan .

Primary Examiner—Thomas M. Dougherty
Assistant Examiner—Nicholas Ponomarenko
Attorney, Agent, or Firm—Cushman Darby & Cushman IP Group of Pillsbury Madison & Sutro LLP

[57] ABSTRACT

A starter is provided that includes a starter motor having an armature core with an armature coil wound therearound and an armature shaft for rotatably holding the armature core. A drive shaft is further provided having a pinion that meshes with a ring gear of an engine. A reduction gear mechanism is interposed between the drive shaft and the armature shaft for reducing the rotation relative to the armature shaft to transmit the reduction rotation to the drive shaft. The reduction gear mechanism has a speed reduction ratio of 6:1 to 10:1.

11 Claims, 21 Drawing Sheets



ABSTRACT

A starter is provided that includes a starter motor having an armature core with an armature coil wound therearound and an armature shaft for rotatably holding the armature core. A drive shaft is further provided having a pinion that meshes with a ring gear of an engine. A reduction gear mechanism is interposed between the drive shaft and the armature shaft for reducing the rotation relative to the armature shaft to transmit the reduction rotation to the drive shaft. The reduction gear mechanism has a speed reduction ratio of 6:1 to 10:1.